Amendments to the Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

Claim 1 (currently amended): A container comprising a body formed by walls and a bottom, the body having ~~in~~ as its ~~greater section~~greatest diameter a dimension d_1 and a neck with an internal diameter d_2, said container being made from a semi-crystalline PET, the body of said container comprising at its bottom at least three feet spaced from each other and being integral with said body,

wherein the ratio weight of the walls to the weight of the bottom is between 3 and 4 and the ratio volume, in ml, of the body of the container per gram of PET of the body is between 80 and 120, and wherein:

the walls of the body have a thickness of less than 100 μm;

the part of the bottom between the feet has a thickness between 100 and 200 μm; and

each foot has a thickness between 50 and 150 μm.

Claim 2 (canceled).

Claim 3 (currently amended): A container according to claim 1, wherein the neck has a wall thickness ~~of~~ between 150 and 250 μm.

Claim 4 (canceled).

Claim 5 (previously presented): A container according to claim 1, wherein the part of the bottom between the feet has a greater thickness than that of the walls.

Claim 6 (currently amended): A packaging assembly comprising:

a container comprising a body formed by walls and a body, having ~~in~~ as its ~~greater section~~greatest diameter a dimension d_1 and a neck with an internal diameter d_2, said container being made from a semi-crystalline PET, the body of said container comprising at its bottom at least three feet spaced from each other and being integral with said body, wherein the ratio weight of the walls ~~on~~ to the weight of the bottom is between 3 and 4 and the ratio volume, in ml, of the body of the container per gram of PET of the body is between 80 and 120, and wherein: the walls of the body have a thickness of less than 100 μm; the part of the bottom between the feet has a thickness between 100 and 200 μm; and each foot has a thickness between 50 and 150 μm;

a product in the container; and

closing means for closing off or distributing the product from the neck;

~~the filled container being substantially incompressible by hand when filled with the product~~.

Claim 7 (previously presented): A packaging assembly according to claim 6, wherein the product is selected from the group consisting of pasty, liquid, semi-liquid, granular and powdered product.

Claim 8 (previously presented): A packaging assembly according to claim 6, wherein said assembly has a high resistance to vertical and/or transverse loads allowing good resistance to transportation.

Claim 9 (original): A packaging assembly according to claim 8, wherein said assembly supports a vertical and/or transverse loading of more than about 100 kg for a container having a weight of about 4 g.

Claim 10 (currently amended): A packaging assembly according to claim 46, wherein the body of the container has a form selected from the group consisting of: a three dimensional shape convenient for gripping, an ovoid, spherical, elliptical and cylindrical shape.

Claim 11 (currently amended): A packaging assembly according to claim 46, wherein the wall thickness of the body, substantially in the middle of ~~its~~ the body is between 30 and 70 μm.

Claim 12 (currently amended): A packaging assembly according to claim 46, wherein the container comprises on its outside a printing made by pad printing.

Claim 13 (currently amended): A packaging assembly according to claim 46, wherein the ratio of d2 ~~on~~ to d1 is between 1:3 and 1:10.

Claim 14 (currently amended): A packaging assembly according to claim 46, wherein the height ratio ~~height~~ of the neck ~~on the height of~~to the body is between 1:1 and 1:4.

Claim 15 (currently amended): A packaging assembly according to claim 46, wherein the ratio weight of the walls ~~on~~ to the weight of the bottom is ~~comprised~~ between 3.4 and 3.8.

Claim 16 (currently amended): A packaging assembly according to claim 46, wherein the ratio volume, in ml, of the body of the container per gram of PET of the body is ~~comprised~~ between 90 and 110.

Claim 17 (currently amended): A process for manufacturing ~~the~~ a container ~~comprising a body formed by walls and a bottom having in its greater section a dimension d_1 and a neck with an internal diameter d_2, said container being made from a semi-crystalline PET, the body of said container comprising at its bottom at least three feet spaced from each other and being integral with said body, the ratio weight of the walls to the weight of the bottom is between 3 and 4 and the ratio volume of the body of the container per gram of PET of the body is between 80 and 120~~according to claim 1, wherein said container is obtained by stretch blow forming of a PET preform with high stretch index in comparison with the classical stretching of a preform.

Claim 18 (currently amended): A ~~packaging assembly~~container according to claim ~~6~~1, wherein the body of the container has a form selected from the group consisting of a three dimensional shape convenient for gripping, an ovoid, spherical, elliptical and cylindrical shape.

Claim 19 (currently amended): A ~~packaging assembly~~container according to claim ~~6~~1, wherein the wall thickness of the body, substantially in the middle of ~~its~~ the body is between 30 and 70 μm.

Claim 20 (currently amended): A ~~packaging assembly~~container according to claim ~~6~~1, wherein the container comprises on its outside a printing made by pad printing.

Claim 21 (currently amended): A ~~packaging assembly~~container according to claim ~~6~~1, wherein the ratio of d2 ~~on~~ to d1 is between 1:3 and 1:10.

Claim 22 (currently amended): A ~~packaging assembly~~container according to claim ~~6~~1, wherein the height ratio ~~height~~ of the neck ~~on the height of~~to the body is between 1:1 and 1:4.

Claim 23 (currently amended): A ~~packaging assembly~~container according to claim ~~6~~1, wherein the ratio weight of the walls ~~on~~ to the weight of the bottom is ~~comprised~~ between 3.4 and 3.8.

Claim 24 (currently amended): A ~~packaging assembly~~container according to claim ~~6~~1, wherein the ratio volume, in ml, of the body of the container per gram of PET of the body is ~~comprised~~ between 90 and 110.